



United States Patent [19]

1)ixon

[11] Patent Number:

5,850,600

[45] Date of Patent:

*Dec. 15, 1998

[54] THREE CELL WIRELESS COMMUNICATION SYSTEM

[75] Inventor: Robert C. Dixon, Palmer Lake, Colo.

[73] Assignce: Omnipoint Corporation, Colorado

Springs, Colo.

[*] Notice: The term of this patent shall not extend

beyond the expiration date of Pat. No.

455/436, 443, 517, 524; 375/200; 370/335,

5,402,413.

[21] Appl. No.: 876,775

[22] Filed: Jun. 16, 1997

Related U.S. Application Data

[63] Continuation of Ser. No. 410,901, Mar. 27, 1995, Pat. No. 5,640,674, Continuation in-part of Ser. No. 682,050, Apr. 8, 1991, Pat. No. 5,402,413.

(51)	Int Cl 6	H04Q 7/00
[31]	Int. Ci.	4551177. 4551517
(52)	IIS CI	455/422; 455/517
[22]	0.5. 01	455/422, 432,
(50)	Field of Search	433/422, 432,
[20]	I leta of Seaton	

[56] References Cited

U.S. PATENT DOCUMENTS

8/1973	Honnia et al.
1/1976	Schilf.
8/1976	Alig et al
5/1977	Willis et al
9/1977	Coussot.
7/1978	Alsup et al
	1/1976 8/1976 5/1977 9/1977

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

2004405	0/1085	Australia	
3934403	9/1905	7,040 7,04	
0150399	8/1985	European Pat. Off H04Q 7/04	
0130377	.0.000	European Pat. Off H04Q 7/04	
0156335	10/1985	European rat. Oh	
0189695	611086	Furnmenn Pal. Oll RU-D 1/20	
	0/1700	HOAR 7/06	
01114222	5/1989	Japan H04B 7/06	

9315573 E/1993 WIPO H04J 13:00 OTHER PUBLICATIONS

Dixon, Robert C., Spread Spectrum Systems, (J. Wiley & Sons, 2d ed. 1984), pp. 1-422.

Eschenbach, Ralph, "Applications of Spread Spectrum Radio to Indoor Data Communications," *Proceedings of the IEEE*, pp. 34.5–1–34.5–3, 1982.

Freret, Payne, et al., "Applications of Spread-Spectrum Radio to Wireless Terminal Communications", Proceedings

of the IEEE, pp. 69.7.1-69.7.4, 1980.
Freret, Payne, "Wireless Terminal Communications Using Spread-Spectrum Radio", Proceedings of the IEEE, 244-248, 1980.

Kavehrad, M., et al., "Performance of Low-Complexity Channel Coding and Diversity for Spread Spectrum in Indoor, Wireless Communication", AT&T Tech. Journal, vol. 64, No. 8, pp. 1927-1965, Oct. 1985.

Kavehrad, M., et al., "Spread Spectrum for Indoor Digital Radio", IEEE Communication Magazine, vol. 25, No. 6, pp. 32-40, Jun. 1987.

(List continued on next page.)

Primary Examiner—Reinhard J. Eisenzopf Assistant Examiner—Marsha D. Banks-Harold Attorney, Agent, or Firm—Lyon & Lyon LLP

[57] ABSTRACT

A wireless communication system including a repeated pattern of cells, in which base station transmitters and user station transmitters for each cell may be assigned a spread-spectrum code for modulating radio signal communication in that cell. Radio signals used in that cell are spread across a bandwidth sufficiently wide that both base station receivers and user station receivers in an adjacent cell may distinguish communication which originates in one cell from another. Adjacent cells may use distinguishable frequencies and distinguishable codes, but it is sufficient if adjacent cells used distinguishable frequencies and identical codes. A repeated pattern of cells allows the codes each to be reused in a plurality of cells.

20 Claims, 2 Drawing Sheets

